

OBEXION UD B3 (SR2) SECURITY SHUTTER

ACCREDITATIONS

- Independently tested by the Loss Prevention Certification Board (LPCB)
- Certified to LPS 1175 Issue 8 B3 (SR2)
- Secured by Design Police Preferred Specifications



CERTIFIED PROTECTION AGAINST:



Forced Entry:
Bodily Force

Mitigation of opportunist intruder attempts
using manual or bodily force including tools.

Catering for risks in the domestic or commercial environment, the Obexion UD B3 (SR2) security shutter is designed to withstand attack by a determined opportunist, using bodily force and mechanically advanced tools of medium size.

Unique to Obexion is the option for a perforated curtain profile, tested and certified to LPS 1175, Issue 8 B3 (SR2) level. Suited to high security commercial properties, where ventilation is required or when planning requests require vision through the shutter, the Obexion UD B3 (SR2) perforated security shutter ensures the security of the building is not compromised.

LOCKDOWN TECHNOLOGY

No auxiliary locking required, manual or electronic.

Unique profiles lock shutter in any stop position - fully closed or otherwise.

Allows external first point-of-entry through the shutter.

OBEXION UD B3 (SR2) SECURITY SHUTTER

SUITABLE APPLICATIONS INCLUDE:

- Medium risk commercial buildings
- Public facilities including schools, universities and community centres
- Retail outlets

APPROVED DIMENSIONS

Minimum certified height: 1.0m Minimum certified width: 0.6m
Maximum certified height: 10.0m Maximum certified width: 8.0m

SHUTTER CURTAIN

Extruded aluminium LockDown profiles.
Finish as delivered: polyester powder coated in standard RAL/BS colour.

BOTTOM RAIL

Reinforced extruded aluminium section with strengthened core.
Finish as delivered: polyester powder coated in standard RAL/BS colour.

CONTROLS

Full range of compatible controls including push button switch, key switch, radio control or integration into existing building management systems and third party alarm.
Safety on close as assessment directs.

OPTIONS

Perforated curtain profile for vision and ventilation.
Anti-cut core for protection against Bespoke risks including grinder attack.

PRODUCT REFERENCE

Obexion UD B3 (SR2) Security Shutter

PERFORMANCE

Certified to LPS 1175 Issue 8 B3 (SR2)

SUITABLE SUBSTRATES:

Internal and External installations complete with sub assembly steel frames as required
Certified installation onto:

- Brickwork
- Blockwork
- Concrete
- Structural Steelwork

FRAMES/GUIDES

Heavy duty guide profiles anchored direct to the structure.
Finish as delivered: polyester powder coated in standard RAL/BS colour.

OPERATION

Motorised to allow controlled ascent and descent.
240v - Low duty cycle or where limited to single phase supply.
415v - High duty cycle or for larger apertures.



Assessed to ISO 9001
Cert/LPCB ref.1075



LPS 1175: Issue 8
Cert No. 1075n

